

## FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

OMB 3067-0077 Expires: June 1984

## **ELEVATION CERTIFICATE**

7648

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

UILDING OW				0	ADDRESS				
STEV			CKENZIE	***	102 14TH	STREET	BELI	LEAIR E	BEACH
				and address if					
					H UNIT D				and that any folio
atement may	be punishat	ole by fine	e or imprison CATION (Co	ment under 18	est efforts to inter U.S. code, Sectio cal Community Pe eyor)	n 1001.			
OM YTINUMMO	PANEL NO.	SUFFIX	DATE OF FIRM	FIRM ZONE	DATE OF CONSTR.	BASE FLO	OD ELEV.	BUILDING IS	
25089	0002	В	6/1/83	A-11	2	10	use depiny	=	<ul><li>□ New/Emergency</li><li>□ Pre-FIRM Reg.</li><li>□ Post-FIRM Reg.</li></ul>
□ ord	inance. The	certifier ft, NGVD	may rely on o . Failure to c	community reca	be constructed in ords. The lowest f uilding at this elev	loor (includi	ng basem	ient) will be	at an elevation
□ □ ord	inance base	d on elev	ation data an	d visual inspec	in compliance wi tion or other reas the community.	th the comm conable mear	unity's flo ns.	ood plain m	anagement
ES NO The	mobile hor	me locate	d at the addre	ess described a ordinance, or	above has been tie in compliance wi	ed down (and th the NFIP S	chored) ir Specificat	n complianc	e with the
	OME MAKE		MODEL		OF MANUFACTU		SERIAL N		DIMENSIONS
2.									<b>X</b>
Sommunity De	armit Officia	l or Rogi	etorod Profes	sional Enginee	r, Architect, or Su	rvevor)	- 1		
CORD		KILLI				70 SUNI	NYDAT.I	E BLVD.	SUITE S
ME GURD	7	KTHHT	ON		ADDRESS 21	70 00111			1
TLE OWNE	R/	2	, CITY	CLEARWA	TER	STATE	FLOI	RIDA	ZIP 346
1	1	7	TAN						
GNATURE	Sanli	20	1.00c	َ بو	DATE 3/02/	'90 <sub>PH</sub>	ONE (81	13) 443	3-7067
ECTION II	4 A20: Lo	artifu that	the building	at the property	cal Community Poveyor.)	ermit Official	or a Regi	istered Profe	essional Enginee
RM ZONE A	1-A30: I co at an	ertify that an elevation elevation	the building for of 13. of 4.5	at the property  1 feet, NGVD  ing at the prop	cal Community Proveyor.)  / location describe // location sea lev  erty location desc	ed above has	or a Regi	est floor (inc	luding basement building site is a
RM ZONES	1-A30:   co at an v, V1-V30:	ertify that an elevation I certify at an ele is at an	the building on of 13. of 4.5	at the property 61 feet, NGVD ing at the prop feet, NGVD	cal Community Poveyor.)  I location describe I location sea levelety location desc I location	ed above has ribed above had ribed above had ribed above had ribed above had level), and	or a Regi	est floor (included at the lottom of the lage grade at described about	essional Enginee luding basement building site is a lowest floor bean the building site
RM ZONE A  RM ZONES A  RM ZONES A  RM ZONES A	1-A30:   certify t	ertify that an elevation I certify at an ele is at an feet, N	the building of 13 of 15 that the build evation of elevation of GENCY PROG	at the property  at the property  at the property  feet, NGVD  ing at the prop  feet,  feet  RAM: I certify  vation of the hig	cal Community Preyor.)  / location describe // location describe erty location desc NGVD (mean sea t, NGVD.  that the building at hest adjacent grade	ed above has rel) and the a ribed above has level), and the property next to the b	or a Regi	est floor (included at the long grade at the long grade at described about	luding basement building site is a lowest floor bean the building site by the building site by the has the lowest feet, NGVD.
RM ZONE A RM ZONES A POOR elevation o RM ZONE AC	1-A30:   contact   contact	ertify that an elevation  I certify at an ele is at an ind EMERO feet, N hat the bu f the high	the building on of 1.5  that the build evation of elevation of GVD. The elevation at the prest adjacent grant of the prest adjacent grant grant of the prest adjacent grant	at the property  1 feet, NG  feet, NGVD  ing at the prop  feet,  lee  RAM: I certify vation of the hig operty location ade next to the t	cal Community Poveyor.)  I location describe VD (mean sea level)  erty location describe NGVD (mean sea t, NGVD.  that the building at the building at the described above has building is	ed above has el) and the a ribed above has level), and the property next to the b	or a Regi	est floor (included at the lottom of the lottom of	luding basement building site is a lowest floor beam the building site bye has the lowest feet, NGVD.
RM ZONES A DOT elevation o RM ZONE AC DOT ELEVATION III	1-A30: I contained and an	ertify that an elevation  I certify at an elevation is at an and EMERO feet, N hat the bu if the highe	the building on of 13. of 4.5  that the build evation of elevation of SENCY PROG GVD. The elevation of the prest adjacent grace.	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, feet RAM: I certify vation of the hig operty location ade next to the t	cal Community Poveyor.)  I location describe VD (mean sea level)  erty location describe NGVD (mean sea t, NGVD.  that the building at the st adjacent grade described above habouilding is	ed above has ribed above has level), and the reproperty next to the bas the lowest flued Profession	or a Regi	est floor (include at the loge grade at described about on of	luding basement building site is a lowest floor beam the building site by the building site is a building site building site is a building site building site building site is a building site is a building site buildi
RM ZONES A CONTROL OF THE CONTROL OF	1-A30: I ce at an an an an an at a an a	I certify that an elevation at the buf the higher knowled base floothe event uman inter unless nors and w	the building ion of 13 of 15 that the build evaluation of elevation of SENCY PROG GVD. The elevation ge, information the passage s of buoyance d. of flooding, vervention meaning are vindows).	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, fee RAM: I certify vation of the hig operty location ade next to the tellon, and belief, of water and s y that would b will this degree us that water v laken prior to t	cal Community Poveyor.)  I location describe VD (mean sea level)  erty location describe VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the standard grade described above habouilding is  tion by a Register of that the building structural compone caused by the form of floodproofing will enter the building the flood to prevent	ed above has rel) and the a ribed above has ribed above has ribed above has level), and the property next to the bas the lowest fifeet, Need Profession is designed leents having lood depths, be achieved ling when flo	or a Reginal or a	est floor (included at the late of the lat	essional Enginee cluding basement building site is a lowest lloor bean the building site ove has the lowest feet, NGVD.  tect) is watertight, wit isting hydrostati impact and upli tion?
RM ZONES A OR ELEVATION III  CERTIFY TO THE CERTIFY	1-A30: I contains an	I certify that an elevation elevation at an elevation at an elevation at an elevation of the higher than the built the event unless more and will the builtions is Y	the building on of 13 of 4 5 that the building of 4 5 that the build evation of elevation of SENCY PROG GVD. The elevation ge, information the passage of buoyancid. Of flooding, we revention mean eneasures are rindows). ding be occurred.	at the property 61 feet, NG 1 feet, NGVD ing at the prop 1 feet, NGVD ing at the prop 1 feet, 1 feet	cal Community Poveyor.)  I location describe VD (mean sea level)  erty location describe VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the standard grade described above habouilding is  tion by a Register of that the building structural compone caused by the form of floodproofing will enter the building the flood to prevent	ed above has rely and the a ribed above has ribed above has ribed above has level), and the property next to the bas the lowest fluents having flood depths, be achieved ing when flood tentry of watting purpose	or a Region of the lower average grant the both average grant location coulding is loor elevated location of the capa pressure with hummods up to aler (e.g.,	est floor (included at the lattom of l	luding basement building site is a lowest floor beam the building site by the building site is a lowest floor building site is a lowest floor building site
RM ZONE A RM ZONES A RM ZONES A RM ZONES A RM ZONES A RM ZONE AC RM ZONE A RM ZONE A RM ZONE A RM ZONES A RM Z	1-A30: I contains an	I certify that an elevation at the built and effect base floothe eventuman interrunless more and will the built the built the built stead. Co	the building on of 13. of 4.5  that the build evation of elevation of SENCY PROG GVD. The elevation grant of the passage of buoyance d. of flooding, we revention mean easures are windows). ding be occurred.	at the property 61 feet, NG 1 feet, NGVD ing at the prop 1 feet, NGVD ing at the prop 1 feet, 1 feet	cal Community Proveyor.)  I location describe VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the standard above has building is the standard componer caused by the food floodproofing will enter the building the flood to prevent the credited for a standard for a st	ed above has ribed above has level), and the property next to the bas the lowest fleet, Ned Profession is designed tents having flood depths, be achieved ing when floot entry of wasting purpossertificates.	or a Reginal steel lowerage grant the both the average grant location coulding is loor elevat IGVD.  Inal Engine so that the capa pressure with humods up to ater (e.g., see and the capa the ca	est floor (incorrade at the lottom of the loge grade at described about the loge grade at described about the building in bility of resist velocities, an intervent of the base floor bolting metals are actual low	luding basement building site is a lowest floor beam the building site by the building site is a lowest floor building site is a lowest floor building site
RM ZONES A RM ZONE AC RM ZONES A RM ZONES A RM ZONES A	1-A30: I contact and an	I certify that an elevation at the higher knowled reable to the event uman interrunless more and will the builtions is Yestead. Co	the building on of 13. of 4.5  that the build evation of elevation of SENCY PROG GVD. The elevation grant adjacent grant the passage of buoyance d. of flooding, we revention mean easures are reindows). ding be occurred. Servention mean meaning be occurred. Servention mean meaning be occurred. Of and AH:	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, feet RAM: I certify vation of the hig operty location ade next to the b ION (Certificat on, and belief, of water and s y that would b vill this degree ns that water v taken prior to t pied as a reside proofing canno the elevation ar	cal Community Proveyor.)  I location describe VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the standard above has building is the standard componer caused by the food floodproofing will enter the building the flood to prevent the credited for a standard for a st	ed above has rel) and the a ribed above has ribed above has ribed above has ribed above has level), and the property next to the bas the lowest fleet, Ned Profession is designed then having flood depths, be achieved ing when floot entry of wasting purpose rertificates.	or a Reginal or a Reginal sthe lowerage grand the average grand the average grand the average grand the capa pressure with humbeds up to ater (e.g., see and the delevation of the delevation of the delevation of the delevation of the lower grand the	est floor (incorrade at the lottom of the loge grade at described about the loge grade at described about the building in bility of resist velocities, an intervent of the base floor bolting metals are actual low	luding basement building site is a lowest floor beam the building site by the building site is a lowest floor building site building s
RM ZONES A	1-A30: I contain an	I certify that an elevation at the higher knowled reable to the event uman interrunless more and will the builtions is Yestead. Co	the building on of 13. of 4.5  that the build evation of elevation of SENCY PROG GVD. The elevation grant adjacent grant the passage of buoyance d. of flooding, we revention mean easures are reindows). ding be occurred. Servention mean meaning be occurred. Servention mean meaning be occurred. Of and AH:	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, feet RAM: I certify vation of the hig operty location ade next to the b ION (Certificat on, and belief, of water and s y that would b vill this degree ns that water v taken prior to t pied as a reside proofing canno the elevation ar	cal Community Proveyor.)  I location described VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the heat adjacent graded described above has building is that the building structural componence caused by the form of floodproofing will enter the building the flood to prevent the caused by the form of floodproofing of the credited for a floodproofing of the credited floodproofing of the credited for a floodproofing of the credited floodproofing of the credi	ed above has rel) and the a ribed above has ribed above has ribed above has ribed above has level), and the property next to the bas the lowest fleet, Ned Profession is designed then having flood depths, be achieved ing when floot entry of wasting purpose rertificates.	or a Region of the lower average grant the average grant the average grant the average grant the capa pressure with hum ods up to alter (e.g., see and the delevation of the capa average grant the capa pressure with hum ods up to alter (e.g., see and the delevation of the capa average grant the cap	est floor (included at the lottom of the building in bility of resist velocities, an intervent of the base flushed bolting mediate actual lowers.	luding basement building site is a lowest floor beam the building site by the building site is a lowest floor building site building s
RM ZONE A  RM ZONES A  RM ZONES A  RM ZONES A  RM ZONES A  RM ZONE AC  RM ZONE	1-A30: I contains an	I certify that an elevation levation le	the building on of 13. of 4.5  that the build evation of elevation of SENCY PROG GVD. The elevation grant adjacent grant the passage of buoyance d. of flooding, we revention mean easures are reindows). ding be occurred. Servention mean meaning be occurred. Servention mean meaning be occurred. Of and AH:	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, Geet, feet RAM: I certify vation of the hig operty location ade next to the the ION (Certificate on, and belief, of water and sey that would be vill this degree ns that water vertaken prior to the pied as a reside proofing canno the elevation ar  BOTH SEC COMPANY	cal Community Proveyor.)  I location described VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the heat adjacent graded described above has building is that the building structural componence caused by the form of floodproofing will enter the building the flood to prevent the caused by the form of floodproofing of the credited for a floodproofing of the credited floodproofing of the credited for a floodproofing of the credited floodproofing of the credi	ed above has el) and the a ribed above has ribed above has ribed above has ribed above has level), and the property next to the best he lowest figure of the profession is designed the having lood depths, be achieved ing when flow atting purpos tertificates.  Floodproofeet (Check One	or a Region of the lower average grant the average grant the average grant the average grant the capa pressure with hum ods up to alter (e.g., see and the delevation of the capa average grant the capa pressure with hum ods up to alter (e.g., see and the delevation of the capa average grant the cap	est floor (included at the lateral later	luding basement building site is a lowest floor beam the building site is a love has the lowest feet, NGVD.  Itect) Is watertight, with isting hydrostati impact and uplition? Tood level octal shields over west floor must be feet, (NGVD)  O. (or Affix Seal)  O. (or Affix Seal)
RM ZONES A	1-A30: I contain an	I certify that an elevation levation le	the building ion of 13 of 14 5  that the build evation of elevation of elevation of The elevation of Ilooding, were the passage sof buoyance of Ilooding, were the elevation meaneasures are reindows).  ding be occurred to and AH:  ECTION II	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, Feet RAM: I certify vation of the hig operty location ade next to the telepoor on, and belief, of water and so y that would b will this degree ns that water vertical price as a reside proofing cannothe elevation ar  BOTH SEC COMPANY KILLION ADDRESS	cal Community Proveyor.)  I location described VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the described above has building is composed by the frequency of floodproofing will enter the building the flood to prevent the credited for a floodproofing of the credited floodproofing of the credited for a floodproofing of the credited floodproo	ed above has rel) and the a ribed above has ribed above has ribed above has ribed above has level), and the property next to the bas the lowest fiftents having flood depths, be achieved ing when floot entry of wating purposertificates.  Floodproofed (Check One	or a Reginate of the lowerage grant the both the average grant location coulding is loor elevated.  Incation coulding is loor elevated in the capa pressure with humods up to atter (e.g., see and the delevation of the location of the locat	est floor (included at the last floor (included at the last floor) and the last floor of the last floor of last fl	essional Enginee cluding basement building site is a lowest floor beam the building site ove has the lowest feet, NGVD.  Itect) is watertight, wit isting hydrostati impact and upli tion? cod level oc- tal shields over vest floor must b feet, (NGVD)  C. (or Affix Seal) C. 3138
RM ZONES A CONTROL OF THE CETTON III  CERTIFICATION CERTIF	1-A30: I contain an	I certify that an elevation levation le	the building ion of 13 of 4 5  that the build evalion of elevation of elevation of the prest adjacent grace of the passage in the passage of the prest of the passage of the prest of the passage of the prest of the pr	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, Feet RAM: I certify vation of the hig operty location ade next to the telepoor on, and belief, of water and so y that would b will this degree ns that water vertical price as a reside proofing cannothe elevation ar  BOTH SEC COMPANY KILLION ADDRESS	cal Community Proveyor.)  I location described VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the standard adjacent graded described above has building is	ed above has el) and the a ribed above has ribed above has ribed above has level), and the property next to the best the lowest figure. Need Profession is designed bents having lood depths, be achieved ing when flow atting purpos tertificates.  Floodproofed (Check One ATES	or a Region of the lower average grant the average grant the average grant the average grant the capa pressure with hum and sup to alter (e.g., see and the delevation of the capa average grant the capa pressure with hum and sup to alter (e.g., see and the delevation of the capa average grant the c	est floor (included at the last floor (included at the last floor) and the last floor of  eer or Archime building in bility of resist velocities, an intervent bottong metal for the base floor bolting metal for the last floor of  ICENSE NO  ICENSE NO  34625	luding basement building site is a lowest floor beam the building site by the building site b
RM ZONES A cor elevation of the alls substanting hydrodyna orces associatly ES IN the answer to completed and IRM ZONES A Completed and IRM ZONES A COMPLETE IN THE CERTIFICATION	1-A30: I contain an	I certify that an elevation levation le	the building ion of 13 of 14 5  that the build evation of elevation of elevation of The elevation of Ilooding, were the passage sof buoyance of Ilooding, were the elevation meaneasures are reindows).  ding be occurred to and AH:  ECTION II	at the property 61—feet, NGVD ing at the prop feet, NGVD ing at the prop feet, Feet RAM: I certify vation of the hig operty location ade next to the telepoor on, and belief, of water and so y that would b will this degree ns that water vertical price as a reside proofing cannothe elevation ar  BOTH SEC COMPANY KILLION ADDRESS	cal Community Proveyor.)  I location described VD (mean sea level)  erty location described NGVD (mean sea level)  that the building at the hest adjacent graded described above has building is	ed above has ribed above has level), and the property next to the bas the lowest fifeet, Ned Profession is designed then having flood depths, be achieved ing when floot entry of what in the entry of what in the entry of what in the entry of what is a chieved in the entry of what is a chieve the entry of what is a chiev	or a Reginate of the lowerage grant the both the average grant location coulding is loor elevated.  Incation coulding is loor elevated in the capa pressure with humods up to atter (e.g., see and the delevation of the location of the locat	est floor (included at the last floor of the last floor at the last floor of the last floor of the last floor intervents the base floor intervents the last floor of last	essional Enginee cluding basement building site is a lowest floor beam the building site ove has the lowest feet, NGVD.  Itect) is watertight, wit isting hydrostati impact and upli tion? cod level oc- tal shields over vest floor must b feet, (NGVD)  C. (or Affix Seal) C. 3138

INSURANCE AGENTS MAY ORDER THIS FORM