OMB 3067-0077 Expires: June 1984



FEDERAL EMERGENCY MANAGEMENT AGENCY NATIONAL FLOOD INSURANCE PROGRAM

ELEVATION CERTIFICATE

This form is to be used for: 1) New/Emergency Program construction in Special Flood Hazard Areas; 2) Pre-FIRM construction after September 30, 1982; 3) Post-FIRM construction; and, 4) Other buildings rated as Post-FIRM rules.

Dr. Na	ancy Dav	W DCI			ADDRESS				
NAME						2 <u>-</u>			
PROPERTY LOC	ouisa Di	cive,	Belleair E	Beach, Fl	orida 3463	5			
					avanablej				
			tates Isla		est efforts to inter	prot the	data available	Lundor	stand that any fal
statement may b	e punishab	le by fine	e or imprisonme	ent under 18	U.S. code, Sectio	n 1001.			(5)
SECTION I EL	IGIBILITY	CERTIFI	CATION (Com Archi	pleted by Loc tect, or Surve	cal Community Pe	ermit Offi	cial or a Regi	stered Pro	fessional Engine
COMMUNITY NO. I	PANEL NO.	SUFFIX	DATE OF FIRM	FIRM ZONE	DATE OF CONSTR.	DASE	FLOOD ELEV.	BUILDING	10
	ANEE NO.	SOFFIX	DATE OF FINM	FINIVI ZONE	DATE OF CONSTR.		Zone, use depth)	BUILDING	☐ New/Emergend
125089	0002	В	3-2-83	"A-11"		10	0.00		☐ Pre-FIRM Reg ☐ Post-FIRM Re
□ □ ordin	nance. The	certifier i ft, NGVD	may rely on cor	mmunity reconstruct the bu	be constructed in ords. The lowest fl uilding at this eleval.	loor (incl	uding basem	ent) will l	oe at an elevation
□ □ ordin	ance based	d on elev	ation data and	visual inspec	in compliance wit tion or other rease the community.	th the co onable m	mmunity's flo	ood plain	management
YES NO The r	mobile hom	e located	d at the address	s described a	bove has been tie	ed down	(anchored) ir	n complia	nce with the
MOBILE HC			MODEL		OF MANUFACTU		SERIAL N		DIMENSIONS
				20,000,00					X
Community Per	mit Official	or Regis	stered Profession	nal Engineer	r, Architect, or Su	rveyor)			
NAME					ADDRESS				
TITLE			CITY			STA	\TE		ZIP
									211
	LEVATION	CERTIF	ICATION (Cert	ified by a Lo	DATE		PHONE cial or a Regi	stered Pro	ofessional Engine
	-A30: I ce	tify that	Arch the building at	itect, or Surv the property	cal Community Pe eyor.) location describe	ermit Office	cial or a Regi	st floor (ir	ncluding basemer
SECTION II EL	-A30: I ce at a	rtify that	Arch the building at on of 10.	itect, or Surv the property	cal Community Pe eyor.)	ermit Office	cial or a Regi	st floor (ir	ncluding basemer
SECTION II EL	-A30: I ce at a an e	rtify that n elevation levation I certify t at an ele	Arch the building at on of 10. of	the property 48 feet, NGVD. g at the property	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea	ermit Officed above the best above t	has the lower ne average gr	st floor (ir rade at th	ncluding basemer e building site is
FIRM ZONE A1-	-A30: I ce at a an e , V1-V30:	rtify that n elevation levation I certify t at an ele is at an e	Arch the building at on of 10. of that the building evation of Elevation of	the property 48 feet, NGVD. at the property feet, Geet, AM: I certify ti	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea	ermit Officed above el) and the libed above level), a	has the lower ne average growe has the board the average	st floor (in rade at th ttom of the ge grade	ncluding basemer e building site is e lowest floor bea at the building s
FIRM ZONES V, FIRM ZONES A, A JOOR Elevation of	-A30: I ce at a an e , V1-V30: A99, AH and	rtify that n elevation l certify t at an ele is at an e d EMERG feet, N at the bu	Arch the building at on of 10 . of that the building evation of ELENCY PROGR. NGVD. The eleviding at the principal strain of the principa	the property 48 feet, NGV g at the property feet, feet AM: I certify to	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea t, NGVD.	ermit Officed above belt above level), a the proper ade next to the proper ade next to the proper ade next to the proper ade t	has the lower ne average growth the average ve has the board the average erty location of to the building	st floor (ir rade at th ttom of the ge grade lescribed a	ncluding basemer e building site is e lowest floor bea at the building s above has the low feet, NGV
FIRM ZONES V, FIRM ZONES A, A loor elevation of get, NGVD. The	-A30: I certify the elevation of at a an earth.	rtify that n elevation I certify t at an ele is at an e d EMERG feet, N at the bu f the hig	Arch the building at on of 10. of 10. that the building exation of 10. EENCY PROGR. NGVD. The elevel ilding at the present adjacent green at the present green green at the present green at the present green at the present green gre	the property 48 feet, NGV feet, NGVD. g at the property feet AM: I certify the ation of the hoperty location rade next to	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea to NGVD). that the building at tighest adjacent graph on described above	ermit Officed above el) and the ibed above level), a the properade next the next the properade next the prop	has the lower he average grant the average grant the average grant the average erty location do to the building e lowest floor feet, NGN	st floor (ir rade at th ttom of the ge grade described a g is	ncluding basemer e building site is e lowest floor bea at the building si above has the low feet, NGV
FIRM ZONES V, FIRM ZONES A, Alloor elevation of the	-A30: I certify the elevation of the loads and the loads are loads are loads are loads.	rtify that n elevation I certify t at an ele is at an e d EMERG feet, N at the bu f the hig OFING C knowledg able to t d effects	Arch the building at on of 10. of 10. of 10. chat the building exation of 10. EENCY PROGRAGE AND The elevitation of 10. EERTIFICATION OF 10. Ge, information, the passage of 10. of buoyancy to the processor of the passage of 10.	the property 48 feet, NGV g at the property feet, NGVD. G at the property feet AM: I certify the ation of the hoperty location of the hoperty locatio	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea to NGVD). that the building at tighest adjacent graph on described above the building is	ermit Officed above el) and the proper ade next to designed and the profess designed and the pro	has the lower he average growth a sthe bound the average erty location do to the building elowest floor feet, NGV sional Engine and so that the growth capable	st floor (in rade at the state of the ge grade described agis relevation /D.	e lowest floor bea at the building s above has the low feet, NGV
FIRM ZONES V, FIRM ZONES A, Alloor elevation of the	A30: I cert at a an element of the company of the c	rtify that n elevation I certify that an ele is at an ele is at an ele is at the bu f the hig OFING C knowledg able to to d effects ase flood ne event of man inter unless m	Arch the building at on of 10. of 10. of 10. that the building exation of 10. ENCY PROGRAGION The elevation at the present adjacent grant	the property 48 feet, NGV feet, NGVD. g at the property feet AM: I certify the ation of the hoperty location and belief, the water and step that would be this degree of that water with the step to	cal Community Pe eyor.) location describe /D (mean sea leve erty location descr NGVD (mean sea to NGVD). that the building at tighest adjacent graph on described above the building is on by a Registere that the building is	ermit Officed above ell) and the bell above level), a the properate next the design of the profess designer ents having when	has the lower he average growth as the bound the average growth has the bound the building elowest flooffeet, NGV sional Engine and so that the ng the capaths, pressures and with human floods up to	st floor (in rade at the state of the ge grade described agis relevation /D. eer or Arcle building billity of residual an interventile base in the base in the state of the s	e lowest floor beat the building stee at the building stee at the building stee at the building stee above has the low feet, NGV n of swatertight, we sisting hydrostas, impact and upontion?
FIRM ZONE A1- FIRM ZONES V, FIRM ZONES V, FIRM ZONES A, oor elevation of elevation of elevation of elevation of elevation of elevation in the certify to the bound of hydrodynam orces associated YES □ NO YES □ NO	A30: I cert at a an expense of the elevation of the eleva	rtify that in elevation elevation. I certify that an ele is at an ele is at an ele is at an ele is at the buf the hig of the highest as elevent eleven	Arch the building at on of 10. of 10. of 10. that the building exation of 10. ENCY PROGRAGION The elevation at the present adjacent grant	the property 4 & feet, NGVD. g at the property feet, NGVD. g at the property feet, feet AM: I certify the ation of the hoperty location and belief, the water and so that would be this degree of that water wen prior to the das a reside ofing cannot	cal Community Pe eyor.) location describe /D (mean sea leve erty location described sea to NGVD. that the building at the building is the building is the building is example on by a Registere that the building is example caused by the floof floodproofing being flood to prevent electron.	ermit Officed above ell) and the bed above level), a the proper ade next to the profess designers havi and dept when the entry of thing pure	has the lower he average grown the average grown the average grown the average grown the average erty location do the building e lowest flooffeet, NGV sional Engine ed so that the ng the capaths, pressures ed with huma floods up to water (e.g.,	st floor (in rade at the state of the ge grade described agriculture) are elevation /D. eer or Arcle building billity of residual are interventing the base to bolting metals.	e lowest floor beat the building stee at the building stee at the building stee at the building stee above has the low feet, NGV n of swatertight, we sisting hydrostas, impact and uplation?
FIRM ZONES V. FIRM ZONES V. FIRM ZONES A., a correlevation of the correl	A30: I center at a an expension of the second and t	rtify that in elevation elevation. I certify that an ele is at an ele is at an ele is at an ele is at the build effects as effood able to the event of the high elevations is YE ead. Com	Arch the building at on of 10. of 10. of 10. that the building existing of elevation of elevation of elevation of elevation of elevation of elevation ge, information, the passage of of buoyancy to flooding, will evention means easures are takendows). ing be occupie S, the floodpronplete both the	the property 4 & feet, NGVD. g at the property feet, NGVD. g at the property feet, feet AM: I certify the ation of the hoperty location and belief, the water and so that would be this degree of that water wen prior to the das a reside ofing cannot	cal Community Pe eyor.) location describe /D (mean sea level) erty location descr NGVD (mean sea level) erty location descr NGVD (mean sea level) that the building at a green described above the building is caused by the floor floodproofing be ill enter the building is effood to prevent the flood floodproofing cell described for rad floodproofing cell described floodproof	ermit Officed above ell) and the bell above level), a the proper ade next to the profess of the each level and the each level at the profess of the each level and the each level at the each le	has the lower he average grown the average grown the average grown the average entry location do the building elowest flooffeet, NGV sional Engine and the capables, pressures ed with huma floods up to water (e.g., posses and the capables).	st floor (in rade at the state of the ge grade described a gis relevation /D. eer or Arcle building bility of reserved as velocities an interventhe base to bolting metals actual local sectors.	e lowest floor beat at the building steement
FIRM ZONES A, a correlevation of the answer to be ompleted and collars.	A30: I center at a an expension of the company of t	rtify that in elevation elevation. I certify that an ele is at an ele is at an ele is at an ele is at the build effects as effocts as effocts are event of the build effects are food in elevent eleve	Arch the building at on of 10	the property 48 feet, NGVD. g at the property feet, NGVD. g at the property feet AM: I certify the ation of the hoperty location and belief, the water and signature with the segment of the segment of the das a reside ofing cannot elevation and segment of the	cal Community Pe eyor.) location describe /D (mean sea level) erty location descr NGVD (mean sea level) erty location descr NGVD (mean sea level) that the building at a green described above the building is caused by the floor floodproofing be ill enter the building is effood to prevent the flood floodproofing cell described for rad floodproofing cell described floodproof	ermit Officed above ell) and the proper ade next of the proper ade next of the profess of the entry of the en	has the lower he average growth as the bound the average growth has the bound to the building e lowest floomfeet, NGN sional Engine and so that the ng. the capaths, pressures ed with huma floods up to water (e.g., posses and the sided Elevation	st floor (in rade at the state of the ge grade described a gis relevation /D. eer or Arcle building bility of reserved as velocities an interventhe base to bolting metals actual local sectors.	e lowest floor beat at the building site is above has the low feet, NGV n of sisting hydrostas, impact and uplation?
FIRM ZONES V. FIRM ZONES V. FIRM ZONES V. FIRM ZONES A., 2000 elevation of 2000 elevation of 2000 elevation of 3000 e	A30: I cert at a an expense of the elevation of the eleva	rtify that in elevation elevation. I certify that an ele is at an ele is at an ele is at an ele is at the build effects as effocts as effocts are event of the build effects are food in elevent eleve	Arch the building at on of 10	the property 48 feet, NGVD. g at the property feet, NGVD. g at the property feet AM: I certify the ation of the hoperty location and belief, the water and signature with the segment of the segment of the das a reside ofing cannot elevation and segment of the	cal Community Pereyor.) location described /D (mean sea level) erty location described erty location described above the building at a great and the building is caused by the floor floodproofing be credited for radial floodproofing certified F	ermit Officed above ell) and the proper ade next of the proper ade next of the profess of the entry of the en	has the lower he average grown the average grown the average grown the average grown the average entry location do to the building the lowest floor feet, NGV sional Engine and so that the ng the capables, pressures and with human floods up to water (e.g., posses and the fred Elevation (inc.)	st floor (in rade at the state of the state	above has the low feet, NGV is watertight, wisisting hydrostas, impact and uplation?
IRM ZONES V. IRM ZONES V. IRM ZONES V. IRM ZONES A, a coor elevation of the cortify to the bralls substantial and hydrodynam corces associated YES \(\text{NOV} \) NO YES \(\text{NOV} \) NO YES \(\text{NOV} \) NO The answer to be completed and could be completed and could be completed. The completed and could be completed and could be completed. The completed and could be completed. The completed and could be completed. The completed and could be completed.	A30: I cert at a an expense of the elevation of the eleva	rtify that in elevation elevation. I certify that at an eleis at an eleis at an eleis at an eleis at the build effects as eflood able to the event of the build ens is YE ead. Com-V30, AC	Arch the building at on of 10. of 10. of 10. that the building elevation of 10. EENCY PROGRAGION The elevation of 10. EERTIFICATION The passage of 10. of flooding, will evention means easures are takendows). ing be occupie S, the floodpronplete both the 10 and AH;	the property 48 feet, NGV feet, NGVD. g at the property feet, NGVD. g at the property feet AM: I certify the ation of the hoperty location and belief, the water and shat would be this degree of that water with the das a reside of ing cannot elevation and believation and shat would be that water with the das a reside of ing cannot elevation and believation and be	cal Community Pereyor.) location described (D) (mean sea level) erty location described (D) (mean sea level) erty location described (D) (mean sea level) that the building at a dighest adjacent gradent (D) (mean sea level) on described above the building is caused by the flood floodproofing be in the component (D) (E) (E) (E) (E) (E) (E) (E) (E) (E) (E	ermit Officed above ell) and the proper ade next of the proper add n	has the lower he average grown the average grown the average grown the average grown the average entry location do to the building the lowest floor feet, NGV sional Engine and so that the ng the capables, pressures and with human floods up to water (e.g., posses and the fred Elevation (inc.)	st floor (in rade at the state of the ge grade described agriculture) are elevation for the base of th	above has the low feet, NGV is watertight, we sisting hydrostas, impact and upontion? fleet, NGVeetal shields over west floor must include the control of t
IRM ZONES V. IRM ZONES V. IRM ZONES V. IRM ZONES A, a coor elevation of the cortify to the beauting the cortification of the cortificat	A30: I center at a anneal anne	rtify that in elevation elevation. I certify that at an eleis at an eleis at an eleis at an eleis at the build effects as eflood able to the event of the build ens is YE ead. Com-V30, AC	Arch the building at on of 10. of 10. of 10. that the building elevation of 10. EENCY PROGRAGION The elevation of 10. EERTIFICATION The passage of 10. of flooding, will evention means easures are takendows). ing be occupie S, the floodpronplete both the 10 and AH;	the property 48 feet, NGVD. 48 feet, NGVD. 48 feet, NGVD. 48 feet, NGVD. 48 the property feet, feet 48 feet, feet 49 feet, feet 40 feet 40 feet 41 feet 42 feet 43 feet 44 feet 45 feet 46 feet 47 feet 48 feet 48 feet 49 feet 49 feet 40 fee	cal Community Pereyor.) location described (D) (mean sea level) erty location described (D) (mean sea level) erty location described (D) (mean sea level) that the building at a dighest adjacent gradent (D) (mean sea level) on described above the building is caused by the flood floodproofing be in the component (D) (E) (E) (E) (E) (E) (E) (E) (E) (E) (E	ermit Officed above ell) and the proper ade next of the proper add n	has the lower he average grown has the bound the average grown has the bound the average entry location do to the building e lowest flood feet, NGN sional Engine and so that the ng. the capaths, pressures ed with huma floods up to water (e.g., boses and the field Elevation (ne)	st floor (in rade at the state of the ge grade described agriculture) are elevation of the state of the base of th	above has the low feet, NGV is watertight, we sisting hydrostas, impact and uplation? If lood level octal shields over west floor must level. If eet, (NGVE)
FIRM ZONES V. FIRM ZONES V. FIRM ZONES V. FIRM ZONES A., Joor elevation of the certify to the bear of the certification of	A30: I center at a anneal anne	rtify that in elevation elevation. I certify that at an eleis at an eleis at an eleis at an eleis at the build effects as eflood able to the event of the build ens is YE ead. Com-V30, AC	Arch the building at on of 10. of 10. of 10. that the building elevation of 10. EENCY PROGR. NGVD. The elevation get adjacent get adjacent get adjacent get adjacent get at a few and a fe	the property 48 feet, NGVD. g at the property feet, NGVD. g at the property feet, Geet AM: I certify the ation of the hoperty location and belief, the water and signature and signat	cal Community Pereyor.) location described (D) (mean sea level) erty location described (Polymean sea level) erty location described (Polymean sea level) that the building at the described above the building is caused by the flood flood proofing be in the caused by the flood flood for the pereyonal component (Polymean Sea level) caused by the flood flood flood for the pereyonal component (Polymean Sea level) caused by the flood flood flood for the pereyonal component (Polymean Sea level) caused by the flood flood flood flood for the pereyonal component (Polymean Sea level) caused by the flood flood flood flood flood flood for the pereyonal component (Polymean Sea level) caused flood f	the properate has the profess designed above the properate has the profess of the	has the lower he average grown has the bound the average grown has the bound the average entry location do to the building e lowest flood feet, NGN sional Engine and so that the ng. the capaths, pressures ed with huma floods up to water (e.g., boses and the field Elevation (ne)	st floor (in rade at the ttom of the ge grade described agris described agris described agris described an interventate base abolting more actual location of the test of the	above has the low feet, NGV is watertight, wiesting hydrostals, impact and uplantion? flood level octal shields over west floor must be feet, (NGVD) flood (or Affix Seal)
FIRM ZONE A1- FIRM ZONES V, FIRM ZONES V, FIRM ZONES A, A floor elevation of get, NGVD. The SECTION III FI Certify to the because substantial and hydrodynam orces associated YES \(\text{NOV} \) YES \(\text{NOV} \) YES \(\text{NOV} \) The answer to be completed and contained	A30: I center at a anneal anne	rtify that in elevation elevation. I certify that at an eleis at an eleis at an eleis at an eleis at the build effects as eflood able to the event of the build ens is YE ead. Com-V30, AC	Arch the building at on of 10. of 10. of 10. that the building elevation of 10. EENCY PROGRAGION The elevation of 10. EERTIFICATION The passage of 10. of flooding, will evention means easures are takendows). ing be occupie S, the floodpronplete both the 10 and AH;	the property 48 feet, NGVD. g at the property feet, NGVD. g at the property feet, Geet AM: I certify the ation of the hoperty location and belief, the water and signature and signat	cal Community Pereyor.) location described (D) (mean sea level) erty location described (Polymean sea level) erty location described (Polymean sea level) that the building at the described above the building is component to the described above the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (P	ermit Officed above ell) and the proper ade next of the proper add n	has the lower he average grown has the bound the average grown has the bound the average entry location do to the building e lowest flood feet, NGN sional Engine and so that the ng. the capaths, pressures ed with huma floods up to water (e.g., boses and the field Elevation (ne)	st floor (in rade at the state of the ge grade described a gis relevation /D. eer or Arcle building polity of restrictions are intervered the base of bolting measurements. The state of t	above has the low feet, NGV is watertight, wiesting hydrostals, impact and uplantion? flood level octal shields over west floor must be feet, (NGVD) flood (or Affix Seal)
FIRM ZONE A1- FIRM ZONES V, FIRM ZONES V, FIRM ZONES A, Joor elevation of the certify to the bear of the certified and concess associated and certified and	A30: I center at a anneal anne	rtify that in elevation elevation. I certify that at an eleis at an eleis at an eleis at an eleis at the build effects as eflood able to the event of the build ens is YE ead. Com-V30, AC	Arch the building at on of 10. of 10. of 10. of 10. that the building evation of 10. EENCY PROGRAGVD. The elevel ilding at the property of the passage of 10. of flooding, will evention means easures are takendows). ing be occupie S, the floodproplete both the 10 and AH; CTION II 11. ITING	the property 48 feet, NGVD. 49 at the property feet, feet 40 coperty location of the hoperty location and belief, to water and significant water and significant water wen prior to the das a reside of ing cannot elevation and significant water wen prior to the das a reside of ing cannot elevation and significant water wen prior to the das a reside of ing cannot elevation and significant water wen prior to the das a reside of ing cannot elevation and significant water	cal Community Pereyor.) location described (D) (mean sea level) erty location described (Polymean sea level) erty location described (Polymean sea level) that the building at the described above the building is component to the described above the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (Polymean sea level) of floodproofing be ill enter the building is tructural component (P	ermit Office d above ell) and the bell and dept elle achieveng when the entry of the bell and b	has the lower he average grown the average grown the average grown the average grown the average entry location do the building elowest floor feet, NGV sional Engine ed so that the ng the capaths, pressures ed with huma floods up to water (e.g., posses and the field Elevation one)	st floor (in rade at the ttom of the ge grade described agais relevation /D. eer or Arcle building bility of reserved at the base of the bolting meter actual location in terver the base of the bolting meter actual location in the first relevation in the base of the bolting meter actual location in the bolting meters actual location in the	above has the low feet, NGV is watertight, we sisting hydrosta s, impact and upontion? flood level octal shields over west floor must be feet, (NGVE) flood (or Affix Seal) G. #1528 P. 5